

# ROADPATCH

## HOT APPLIED BITUMINOUS POTHOLE REPAIR PRODUCT

Roadpatch is a hot applied bitumen based compound, which can be trafficked within 15-30 minutes of application (depending upon ambient temperature). It is ideal for filling potholes, defects, trenches of varying depths, and is especially suited for pre-surface dressing repairs to asphalt surfaces. Roadpatch can also be used for repairing areas around drains and iron works etc. Ideal for use on all classes of highways.

### BENEFITS:

- Application not seasonally affected
- Fast cure time
- Economical
- Compatible with flexible road surfaces
- Impervious
- Speed of application

### IMPORTANT NOTES:

Storage and handling: Packed in 25kg silicone lined paper bags, shelf life approx. 12 months, protect from sub-zero temperatures.



### PHYSICAL PROPERTIES

Form	Bituminous
Colour	Black
Specific Gravity	2.2
Aggregate PSV	55 +
Application Temp. Range	190 - 210°C
Curing Time	15 - 30 mins
Application Depth	20mm +
Compression @ 20°C (10 mm/min)	500 N +

**Disclaimer:** All products should be used in accordance with the manufacturer's instructions. No responsibility can be taken by the manufacturer where conditions of use are beyond our control. Materials are sold only on the basis of conforming to specification, but without warranty expressed or implied in law or in fact of merchantability or fitness for a particular purpose and upon the condition that purchasers make their own tests to determine the suitability of such products for their particular purpose. Issue no: 5 - 23.1.21

Speak to our experts, contact us today

T: +44 (0) 1508 536 360 | E: [info@roadtechs.net](mailto:info@roadtechs.net) | [www.roadtechs.net](http://www.roadtechs.net)